

Earth Terminals

RT Series :ROBUST Earth Terminals

■ Features

1. Its unique structure prevents contact deformation.
2. We have prepared a lineup with the same spring shape but with varying heights that can be adjusted by changing the height of the side area.
3. Due to the common board pattern, height differences can easily be reset. (415CPB-167-XXF, 415CPB-168-XXF)
4. The space provided between the mounting and spring areas prevents solder lifting.
5. The embossed taping for the automatic mounter by SMT is available.

■ Specification


- Contact :Single Contact Design
- Height :1.0 to 3.4mm (Different by Part No.)
- Stroke :0.2 to 0.7mm (Different by Part No.)
- Contact Pressure :0.25 to 1.0N (Different by Part No.)
- Packaging :Emboss Taping

Part No.	Contact Pressure	Working Height	Rating
415CPB-165-52F	0.25 to 0.6N	0.45 to 0.75	3A max., 5V DC
415CPB-167-□□F	0.3 to 1.0N	0.6 to 1.4	2A max., 5V DC
415CPB-168-□□F	0.3 to 1.0N	1.2 to 3.2	2A max., 5V DC


□□:Dimensions A and B are different by Part No. Please contact us.



415CPB-165-52F



415CPB-167-□□F



415CPB-168-□□F

